



## Two Stage Compounding Extruder Machine for Plastic Shoe Sole Material

Our Product Introduction

for more products please visit us on [extrudergranulator.com](http://extrudergranulator.com)

### Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: HLD
- Minimum Order Quantity: 1
- Price: \$28,000



### Product Specification

- Plastic Processed: PE, PP, ABS, Xps, WPC, Polystyrene, PA, EVA, EPS, PET, PC, FRPP/PVC, HDPE, PPR, Wood-plastic, ABS/PP, HDPE/PP, PE/PP, LLDPE, LDPE, Polylactic Acid
- Application: Granules, Pelletizing
- Screw Design: Single-screw
- Screw Material: 42CrMo
- Screw Diameter (mm): Other/Customized
- Screw L/D Ratio: Customised
- Screw Speed (rpm): 600 Rpm, 600 Rpm
- Voltage: Customized
- Dimension(l\*w\*h): Customized
- Power (kw): 60
- Warranty: 1 Year
- Key Selling Points: High Productivity
- Video Outgoing-inspection: Provided



### More Images



### Product Description

# Product

## Two Stage Extruder Machine

Two Stage Twin Screw+Single screw Extruder granules Machine. It is suitable for most polymer compounding production, which features simple structure, easy operation and convenient maintenance. Common, will be matched with the Kneader machine. Use two stage extruder machine for Black masterbatch /Cable material / 80% CaCo3 filler and so on. Suitable for projects with large output. The two-stage compounding extruder is so favored by its good production quality, higher output and lower energy consumption. It is particularly applicable to produce the heat-sensitive material PVC, POM, XLPE, etc.

Model	Twin screw L/D	Output
H60-120	38:1/ 40:1/ 44:1/ 48:1	400~700kg/h
H65-150	38:1/ 40:1/ 44:1/ 48:1	600~900kg/h
H75-180	38:1/ 40:1/ 44:1/ 48:1	800~1300kg/h
H95-200	38:1/ 40:1/ 44:1/ 48:1	1200~1500kg/h



## Two Stage Extruder



## Use

Given the material and recipes, We can offer an array of compounding systems with options for compressing or molding a material into pellet form. These pellets are used as follows



**Filler Masterbatch**

Filler Masterbatch are concentrates of  $\text{CaCO}_3$  or Talc or  $\text{BaSO}_4$  in a polymer base.



**Color Masterbatch**

Color masterbatch is used for any polymer and all kinds of product.



Photo provided by GM Color (Poland)

**Additive Masterbatch**

Additive Masterbatch are used in a wide variety of application.



## Our Exhibition



## Logistics



Small samples and materials, we will send it by international express. Large machinery and equipment, we will send by sea. Normally, the logistics time is 10 to 40 days. We will pack our machines in wooden cases.

## FAQ

**1:What machines are they mainly producing?**

Plastic twin screw extruder machine and accessories and other granules making machine.

**2:How much time it takes to customize?**

10~40days

**3:How to pay?**

You can pay with Ali or TT go to the bank.

**4 How long is the warranty?**

1year

### 5:How to Contact Us?

you can E-mail to us.We will provide the technology to know, online.

 **Nanjing Henglande Machinery Technology Co., Ltd.**

 +86 15251884557

 [jayce@hldextruder.com](mailto:jayce@hldextruder.com)

 [extrudergranulator.com](http://extrudergranulator.com)

NO.11,Qinghu Road,Hushu Town,Jiangning District,Nanjing,china.